

PCT

WORLD INTELLECTUAL PRO  
International

INTERNATIONAL APPLICATION PUBLISHED UNDER



(51) International Patent Classification 6 :

G06F 17/40, G01S 3/02

A1

(11)

WO 9605562A1

(43) International Publication Date: 22 February 1996 (22.02.96)

(21) International Application Number: PCT/US95/10375

(22) International Filing Date: 14 August 1995 (14.08.95)

(30) Priority Data:

08/291,564

16 August 1994 (16.08.94)

US

(71) Applicant: WORLDWIDE NOTIFICATION SYSTEMS, INC.  
[US/US]; Suite 500, 4508 Dartmoor Drive, Marietta, GA  
30067 (US).

(72) Inventors: FARMAKIS, Tom, S.; 100 Indian Creek Trail,  
Sharpsburg, GA 30277 (US). ROUTSONG, Russell, D.;  
706 Bookman Point, Peachtree City, GA 30269 (US).


(74) Agents: BRAKE, R., Edward et al.; Howrey & Simon, 1299  
Pennsylvania Avenue, N.W., Washington, DC 20004 (US).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH,  
CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE,  
KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN,  
MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,  
TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE,  
CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT,  
SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML,  
MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ,  
UG).

Published

With international search report.

(54) Title: SATELLITE BASED COLLISION AVOIDANCE SYSTEM



(57) Abstract

This invention provides a method and apparatus to provide coordinated evasive maneuver commands to aircraft to avoid collision. More specifically, the invention comprises a gps system to determine the location of aircraft, control logic (68) to calculate evasive maneuvers, display aircraft tracking information, coordinate the evasive maneuver with the intruding aircraft, and give a synthetic voice warning and command to the pilots.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## SATELLITE BASED COLLISION AVOIDANCE SYSTEM

BACKGROUND OF THE INVENTION

This invention relates generally to an automatic collision avoidance control and alert system for tracking and directing aircraft and other vehicles for collision avoidance. More specifically, the invention is an improved collision avoidance system for use in automatically alerting a pilot of a collision threat and coordinating an evasive maneuver between aircraft. The expected advantages of such a system is improved collision avoidance, elimination of false collision alarms and an increased target tracking capacity. The present invention is directed to such an automatic vehicular-based system for automatically providing collision avoidance.

Since the advent of aviation it has been desirable to avoid aircraft collisions and near misses. Traditionally, pilots have used a wholly manual method, i.e. visually identifying other aircraft and flying to avoid a collision. Such a system is susceptible to human error and is wholly unworkable in low visibility conditions or within crowded airspace.

The use of a ground based air traffic control (ATC) system, two-way voice radio communications and RADAR greatly enhance the identification and control of aircraft to avoid collisions. Two-way voice radio communication allows aircraft to communicate with one another and the ATC operator to avoid potential conflicts. RADAR, both on-board aircraft and at ground based ATC facilities provides an operator intensive technique for avoiding aircraft collisions. In the present ATC system the ATC operator coordinates the location, altitude, and track of all aircraft within her assigned control area by communicating with the aircraft over two-way voice radio. Present ATC systems consist of a network of airport terminal area and enroute surveillance radar systems. These systems consist of both primary and secondary RADAR systems and computers that display usable data for the control of air traffic in the national and international airspace systems.

The basic ATC RADAR system consists of Primary RADAR and secondary RADAR. Primary RADAR operates by transmitting a high power, highly directional radio pulse at a known azimuth (direction, in degrees from North) from a rotating antenna and measures the time it takes to receive the reflected signal from an object (aircraft) in space back to the point of transmission. This time factor determines the range in nautical miles from the radar site to the target.

The direction of the target is determined by the antenna azimuth from which the signal is received. The limitations of using only this system result in the loss of targets because of the difficulty in detecting weak reflected RADAR return signals attenuated by atmospheric conditions and the difficulty in operating a  
5 synchronized height finding radar.

Secondary RADAR known as the Air Traffic Control Radar Beacon System (ATCRBS) utilizes cooperative equipment (a radio receiver/transmitter or transponder) located in the target aircraft to replace the conventional radar's passive reflected return signal with an active reply signal. Like a conventional  
10 high power radar, ground based secondary radar transmits a highly directional pulse from a rotating antenna that is usually synchronized with the primary radar antenna. The secondary radar pulse is called the interrogating signal. The interrogating signal requires much less power than conventional radar because secondary radar relies on an active return signal from the target aircraft. In  
15 response to receiving the interrogating signal the cooperative aircraft transponder automatically transmits a distinctive reply signal back to the secondary radar's antenna. The secondary radar measures the time between the interrogating signal transmission and the transponder reply signal and, like the reflected return in primary radar, uses this time delay to determine the range of the target aircraft.  
20 The direction of the target aircraft is determined by the antenna azimuth from which the reply signal is received. The secondary radar's cooperative transponder improves on the conventional radar's passive reflective return by encoding additional information in the transponder reply signal. The additional information includes an aircraft identification number and the aircraft pressure  
25 altitude. For example, Delta flight 195 to Dallas (Dal195) is requested by ground based ATC to squawk "4142". In response, the aircraft pilot manually dials in "4142" at the aircraft transponder control panel. The transponder control logic can now encode the assigned four digit identification, e.g. "4142", on the transponder reply signal. The aircraft's transponder can also be connected to the  
30 aircraft's pressure altimeter to enable the transponder control logic to encode the aircraft pressure altitude on the transponder reply signal. The aircraft transponder reply signal containing the encoded aircraft identification and pressure altitude is processed by ground based computers for display on the ATC operator's radar screen. The ATC operators usually provide specific flight

instructions to aircraft to avoid flight conflicts and warn aircraft of other nearby aircraft. In large aircraft, active on-board conventional nose RADAR may also identify aircraft that are in front of the large aircraft.

RADAR, however, has a number of disadvantages. Radar systems, even  
5 secondary radar, provides limited range and accuracy in the determination of the location and altitude of an aircraft. The range of radar is inherently limited due to obstacles in the line of sight of the radar, curvature of the earth, atmospheric conditions, etc., and is subject to provide false readings or ghosts. RADAR may also fail to provide sufficient target resolution at the critical near collision phase  
10 where target aircraft are close together. Radar coverage is not available in many areas of the world, and is not available at all altitudes in the United States.

The presently used and Federal Aviation Administration (FAA) approved aircraft collision avoidance system is known as the Traffic Alert and Collision Avoidance System (TCAS). The TCAS is an airborne traffic alert and collision  
15 avoidance advisory system that operates without support from ATC ground stations. TCAS detects the presence of nearby intruder aircraft equipped with transponders that reply to secondary radar interrogating signals. TCAS tracks and continuously evaluates the threat potential of these aircraft in relation to one's own aircraft, displays the nearby transponder-equipped aircraft on a traffic  
20 advisory display, and during threat situations provides traffic advisory alerts and vertical maneuvering resolution advisories (RA) to assist the pilot in avoiding mid-air collisions. A TCAS has a transmitter, a transmit antenna, a transponder, one or two directional receiver antennae, a control interface, display unit(s), and a signal/control processor.

25 A TCAS determines the location of other aircraft by using the cooperative secondary radar transponders located in other aircraft. A TCAS transmitter asynchronously polls for other aircraft with an active L-band interrogating signal, i.e. at the same frequency as the ground based secondary radar interrogating signal. The TCAS interrogating signal, however, is an omni-directional signal  
30 whereas the ground based secondary radar signal is highly directional. When a target aircraft's cooperative transponder receives a TCAS interrogating signal the transponder transmits a reply signal. By using RADAR timing principals, the interrogating TCAS can measure the time between the interrogating signal transmission and transponder reply to determine the approximate range of the

intruder aircraft. By using direction finding antenna techniques, the interrogating TCAS determines the relative direction of the transponder reply signal with a fixed directional antenna array and the TCAS signal processor. The TCAS omnidirectional interrogating signal causes all secondary radar cooperative  
5 transponders within receiving range to reply, therefore, the TCAS signal processor uses a complex receiver input blanking scheme to locate and distinguish the multiple reply signals. For example, the TCAS interrogating signal is coordinated with the TCAS signal processor to allow the TCAS signal processor to create a variable width receiver blanking signal. The variable width receiver blanking  
10 signal is used to progressively exclude "closer" transponder reply signals. This allows the TCAS interrogator signal and transponder reply signal processor to receive transponder replies from progressively further away aircraft.

The TCAS control logic uses the range, relative bearing, and pressure altitude determined by the interrogating signal and secondary radar transponder  
15 replies to track intruder aircraft. The intruder track is displayed on the TCAS display. The TCAS display is a VDU typically mounted on the aircraft front instrument panel. TCAS tracking information, graphically depicting the relative distance and relative bearing of intruder aircraft, greatly assists a pilot in identifying and visually acquiring intruder aircraft. The TCAS control logic also  
20 calculates the "tau" of the intruder aircraft. "Tau" is the ratio of range to range-rate, and represents the time to intercept for two aircraft on a collision course, assuming un-accelerated relative motion. The TCAS compares the "tau" with predetermined collision threat parameters. If an intruder aircraft falls within these parameters a TCAS declares the intruder aircraft a threat. The pre-determined  
25 collision threat parameters delineate the intruder aircraft "tau" into four threat categories. In most categories the TCAS merely brings the intruder status to the pilot's attention with an audible alert on the aircraft intercom. In the highest category the TCAS creates an evasive maneuver to vector both aircraft to increase the vertical separation between the aircraft. For situations where one's own TCAS  
30 equipped aircraft and another TCAS equipped aircraft are declared collision threats to each other, the TCAS in each aircraft in conjunction with their secondary radar transponder subsystem, establish an air-to-air resolution advisory in both aircraft. The resolution advisory is displayed on the TCAS display unit. The resolution advisory is a directive to the pilots to either climb or descend.

The TCAS system, however, suffers from a number of disadvantages. First, the TCAS system issues numerous false alarms and/or erroneous commands or instructions. Erroneous commands and false alarms may increase the probability of collision by erroneously instructing the aircraft to fly nearer the intruding aircraft, or to descend when the aircraft is already at a minimal altitude. Such false alarms and erroneous instructions are prevalent during take-off and landing where the TCAS has particular trouble discerning signals from the many nearby aircraft. Such false alarms, in addition to distracting the pilot, can create distrust in the entire TCAS system. This distrust can cause a pilot to hesitate or ignore a valid evasive maneuver or resolution advisory command because the pilot mistakenly believes the command is just "another" TCAS false alarm. Another source of TCAS false alarms is an overly simplistic collision prediction algorithm, i.e. the "tau" calculation. The TCAS collision alert algorithm does not account for whether an aircraft is proceeding on its present course or is leveling off at a predetermined altitude, i.e. it assumes an un-accelerated aircraft track. Such problems are reported by Dave Davis and Michael Sangiacomo in Jets in Jeopardy: False Warnings from Midair Collision System have Led Airline Pilots to Near Catastrophe, The Plain Dealer, July 14, 1994, at 1A. The Plain Dealer investigative reporters discovered that within the span of a few months, TCAS false alarms nearly caused several aircraft disasters. Furthermore, some pilots state that the TCAS is so unreliable in crowded airspace that the TCAS does not work at all under these conditions.

Second, TCAS requires an elaborate direction finding antenna array and processing logic to find an intruder's relative direction. Such a system is inherently susceptible to multipath errors, noise clutter, and other spurious signals. Again, this can create false alarms, false returns or phantom aircraft and incorrect tracking displays.

Third, intruder pressure altitude information is only transmitted from the TCAS transponder when the TCAS is connected to a pressure altimeter. Thus, the existing TCAS system cannot detect a collision danger with an aircraft that does not have a functional pressure altimeter. Moreover, the pressure altimeter itself is subject to the risk of human error. A pressure altimeter must be periodically adjusted to compensate for local atmospheric conditions and elevations. If the pilot does not make the proper altimeter adjustment then the TCAS transponder

will transmit erroneous altitude information. The lack of altitude information or incorrect altitude information seriously undermines the accuracy of the TCAS system.

5 Fourth, the TCAS interrogator/transponder protocol requires an elaborate antenna sidelobe suppression and receiver blanking technique to block transponder replies from close aircraft and to allow the system to poll aircraft further away. Such a system is again susceptible to noise, signal clutter, other spurious signals and multiple aircraft transponder within the same transponders reply time frame.

10 ATC systems have been proposed that would use the global positioning system (GPS) satellites. Such a proposed system is discussed in chapter 12 of Logsdon, The Navstar Global Positioning System, Von Neistrand Reinhold (1992). In The Navstar Global Positioning System, Logsdon discusses the proposed use of GPS receivers on board aircraft, wherein the aircraft transmits its GPS aircraft  
15 vector to air traffic controllers for display on the air traffic controllers' screen. Logsdon also discusses another proposed navigation system based on the proposed Geostar satellites. In the Geostar system, when an aircraft needs to know its location, interrogation pulses are transmitted from the aircraft to three Geostar satellites, which immediately relay the request to a centrally located  
20 computer on the ground. The ground computer determines the location of the aircraft and relays the location back to the aircraft using one of the satellites. The Geostar system was described as also being able to relay short telegram messages between two Geostar subscribers (aircraft) using one of the satellites. This proposed Geostar navigation system suffers from a number of drawbacks. For  
25 example, as with TCAS, each aircraft does not provide its location, speed, heading to other aircraft. Instead, in Geostar, aircraft must rely on the extensive ground-based processing before the aircraft can obtain its own position. Furthermore, the Geostar system provides no technique for reducing collision of aircraft.

Other navigation aides are know to the art. In the 48 contiguous United  
30 States, most instrument navigating is done with the aid of a VHF Omnidirectional Range (VOR) receiver for using the VHF radio signals emitted by the ground based VOR transmitters. Virtually all enroute navigation and many instrument approaches use these signals, which are broadcast in the frequency range 108.0 to 119.0 Mhz. The VOR signal is a blinking omnidirectional pulse, and has two



parts: a reference phase signal and the variable phase signal. It is transmitted in such a way that the phase between these two signals is the same as the number of degrees the receiving aircraft is from the VOR station. The VOR receiver and equipment uses the signals to determine the aircraft direction, or course, from the

5 VOR.

An additional navigation aide is known as Distance Measurement Equipment (DME). DME uses two-way (interrogation and reply) active spherical ranging to measure the slant range between the aircraft and the DME transmitting station. Many pilots and navigators vector airplanes from waypoint to waypoint

10 using the signals from VOR/DME, rather than traveling in a straight line. As a result, aircraft are not traveling the shortest distance, causing increased fuel usage and increased travel time. Also, routes along the VOR/DME stations become heavily traveled resulting in increased probability of mid-air collisions.

In addition, many aircraft employ so-called Instrument Landing Systems (ILS) for performing precision landings. ILS includes several VHF localizer transmitters that emit focused VHF signals upwardly from the airport to provide horizontal guidance to the aircraft and its autopilot systems. ILS also includes a UHF glideslope transmitter that radiates a focused UHF signal that angles downwardly across the runway to provide vertical guidance. While ILS provides

15 an effective technique for precision landings, such ILS precision landings are not possible where the airport does not include such localizer and glideslope transmitters.

20

#### SUMMARY OF THE INVENTION

Accordingly, to is an object of the present invention to provide an

25 improved automatic collision avoidance system based on satellite navigation signals.

It is a further object of the present invention to provide an improved automatic collision avoidance system based on the global positioning system and a direct radio wave inter-aircraft radio network synchronized with the GPS

30 precision clock.

It is yet another object of the present invention to provide an improved automatic collision avoidance system based on the global positioning system that is backward compatible with existing collision avoidance systems.

It is yet another object of the present invention to provide an improved

automatic collision avoidance system based on the global positioning system, a direct radio wave multipoint network synchronized with the GPS precision clock, and ground based pseudo-satellites navigation enhancement signals.

It is yet another object of the present invention to provide an automatic collision avoidance system based on the global position system, a direct radio wave multipoint network synchronized with the GPS precision clock, and communication with fixed navigation obstructions equipped with a collision avoidance beacon.

It is yet another object of the present invention to provide an automatic collision avoidance system based on the global positioning system, a direct radio wave multipoint network synchronized with the GPS precision clock, and an interface with the automatic navigation system or auto-pilot to control the anti-collision maneuver without pilot intervention.

In accordance with the present invention, an improved automatic collision avoidance system for guiding vehicles is provided which includes a sensing system for receiving GPS signals, an apparatus for translating the GPS signals to determine the GPS location, GPS altitude and track, a transceiver system for operating a multipoint direct radio wave protocol synchronized to the GPS precision clock for transmitting the GPS position and receiving other aircraft GPS positions, extrapolating the track of all nearby aircraft and determining whether any aircraft pose a collision threat, control logic to create evasive maneuvers to separate aircraft that are within a predetermined collision track tolerance, and establishing a data link between aircraft to coordinate the evasive maneuver.

#### BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciate of the present invention and many of the attendant advantages thereof will be readily obtained as the invention becomes better understood by references to the following detailed description when considered in connection with the accompanying drawings.

FIGURE 1 is a schematic diagram of an improved automatic collision avoidance system in accordance with a preferred embodiment of the present invention.

FIGURE 2 is an overall functional block diagram of the improved automatic collision avoidance system of FIGURE 1.

FIGURE 3 illustrates the relative display mode format for the display unit

of the improved automatic collision avoidance system of FIGURES 1 and 2.

FIGURE 4 illustrates the pseudo three dimensional display mode format for the display unit of the improved automatic collision avoidance system of FIGURES 1 and 2.

5       FIGURE 5 illustrates the control panel for the control unit of the improved automatic collision avoidance system of FIGURE 1 and 2.

FIGURE 6 is a schematic diagram illustrating a set of steps to operate the improved automatic collision avoidance system illustrated in FIGURES 1 and 2.

10       FIGURE 7 is a diagram illustrating the data message block used to communicate between an improved automatic collision avoidance system and another improved automatic collision avoidance system.

FIGURE 8 illustrates a sequence of steps which may be performed to operate the multipoint direct radio protocol used in the improved automatic collision avoidance system.

15       FIGURE 9 illustrates a sequence of steps which may be performed to operate the surveillance and tracking function to operate the improved automatic collision avoidance system of FIGURE 1 and 2 by performing the steps of the function block shown in FIGURE 6.

20       FIGURE 10 illustrates a sequence of steps which may be performed to operate the threat potential and evaluation function to operate the improved automatic collision avoidance system of FIGURE 1 and 2 by performing the steps of the function block shown in FIGURE 6.

25       FIGURE 11 illustrates a sequence of steps which may be performed by the traffic advisory display function to operate the improved automatic collision avoidance system of FIGURE 1 and 2 by performing the steps of the function block shown in FIGURE 6.

30       FIGURE 12 illustrates a sequence of steps which may be performed by the evasive command generator function to operate the improved automatic collision avoidance system of FIGURE 1 and 2 by performing the steps of the function block shown in FIGURE 6.

FIGURE 13 is a schematic diagram of an automatic collision avoidance system in accordance to a second seagoing vessel embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

Referring to the drawings in detail wherein like numerals indicate like elements, Figure 1 is a schematic diagram of an improved automatic collision avoidance system in accordance with the preferred embodiment of the present invention. The improved automatic collision avoidance system is called the satellite tracking alert resolution system (STARS). The STARS is a self contained airborne collision avoidance system that does not require any ground based support. The aircraft 8 is equipped with a STARS 10. An antenna 12 may be used to receive GPS signals from orbiting GPS satellites a few of which are illustrated as 14, 16, 18, and 20. An optional antenna 22 may be used to receive pseudo-satellite signals from ground based stations 24. Pseudo-satellite signals may be used to increase the navigational accuracy of the STARS. The STARS 10 processes the satellite navigational signals to determine a GPS position and GPS altitude for the aircraft 8. A GPS position is usually represented in the traditional navigational coordinate system in hours, minutes, and seconds 26 from the prime meridian and degrees from north or south of the equator on the so called parallels 28. It is understood that any coordinate system can be used to practice the present invention and is within the scope of the present invention to convert between coordinate systems. The STARS 10 sequentially determines the GPS position and GPS altitude of the aircraft 8. The STARS 10 uses the sequential GPS positions and GPS altitude to determine the track 30 of the aircraft 8. The aircraft track 30 represents the velocity vector of the aircraft 8.

The STARS 10 transmits the aircraft 8 position and the aircraft 8 track 30 on the STARS transceiver antenna 32 and optional antenna 34. The STARS transmit power is calibrated with the STARS receiver signal threshold to enable an effective range of approximately 50 miles 36. It is understood that STARS 10 transmit power and receiver signal thresholds can be adjusted to allow the STARS to operate in a variety of range modes. Moreover, it is understood that the antenna footprint 32 and 34 may be adjusted to allow the STARS 10 to project the STARS transmit signal further, e.g. 80 miles, in front of the aircraft 8 and increase receiver sensitivity to targets in front of the aircraft 8.

An intruder aircraft 38 is equipped with a STARS identical to the STARS 10 and antenna 32, 12, 22 and 34 of aircraft 8. Likewise, the intruder aircraft 38 STARS also sequentially determines aircraft 38 GPS position, GPS altitude and track 40. The intruder aircraft 38 STARS is also transmitting the intruder aircraft

GPS position and track on the STARS transceiver. The intruder aircraft 38 STARS transceiver transmit time is synchronized to the aircraft 8 STARS 10 transceiver transmit time with a time division multiple access protocol (TDMA), discussed in detail below. The protocol may maintain synchronization with a common timing  
5 source derived from the GPS precision clock. The GPS precision clock is determined from the GPS satellite 14, 16, 18, 20 and pseudo-satellite 24 signals. It is understood that other clocking means such as an internal crystal oscillator may be used to synchronized the TDMA protocol.

The aircraft 8 STARS transceiver antenna 32 and optional antenna 34  
10 receives the transmit signal from intruder aircraft 38. As described in substantive detail below, the aircraft 8 STARS extrapolates the track of aircraft 8 and aircraft 38. It is understood that STARS may extrapolate tracks from a plurality of aircraft. It is also understood that the "tau" as known to the collision avoidance art, i.e. range over range-rate, calculation is within the scope of the present invention and  
15 may be used in place of an extrapolated track. The aircraft 8 STARS 10 determines the closest distance between the extrapolated track 44 of aircraft 8 and extrapolated track 42 of aircraft 38. The STARS compares the closest distance between the extrapolated tracks to pre-determined safe distance and altitude parameters. Generally, the process of determining the closest distance between  
20 the aircraft 8 and 38 is an iterative process which is performed by a sequence of steps programmed into a microcomputer. Consequently, the process of extrapolating tracks, comparing the tracks and determining whether the aircraft 8 will maintain a safe distance from all intruder aircraft is continuously repeated as the aircraft 8 travels through the air. The intruder aircraft 38 simultaneously and  
25 independently performs an extrapolation of aircraft tracks 42 and 44, compares the tracks, and determines whether the aircraft 38 will maintain a safe distance from all intruder aircraft.

If aircraft 8 STARS 10 determines that the aircraft 8 will pass by another aircraft, for example aircraft 38, with less than the predetermined safe distance  
30 and attitude parameters, then the STARS 10 will generate an evasive maneuver 48 for aircraft 8 to increase the vertical distance between aircraft 8 and aircraft 38. A preferred technique for calculating the evasive maneuver 48 is discussed in substantive detail below but, in general the higher aircraft will be directed to climb and the lower aircraft will be directed to descend. A data link is established,

using the STARS transceivers, between the aircraft 8 and 38 to coordinate the evasive maneuver 48. The preferred data link technique is discussed in substantive detail below but, generally, aircraft 38 receives the aircraft 8 evasive maneuver and aircraft 38 generates an opposite evasive maneuver 50. Aircraft 38 STARS transmits the opposite evasive maneuver to aircraft 8 STARS 10. Upon receipt of aircraft 38 STARS opposite evasive maneuver, aircraft 8 STARS 10 in the preferred embodiment alerts and displays the evasive maneuver 48 to the aircraft 8 pilot. Aircraft 8 STARS 10 in the preferred embodiment also transmits that the evasive maneuver is executing to aircraft 38. Aircraft 38, upon receipt of the evasive maneuver executing message alerts and displays evasive maneuver 50 to the aircraft 38 pilot. As discussed in substantive detail below, the STARS has numerous advisory and evasive maneuver commands to resolve numerous possible scenarios between approaching aircraft. Additionally, the communication process between different STARS may include information concerning aircraft identification, status, telemetry from instrumentation, and altitude window information. The altitude window is an altitude set at the STARS control panel by the pilot that indicates the altitude at which the pilot will level off. As discussed more fully below, this information in general may be used to calculate appropriate evasive commands for the aircraft. Thus, the STARS altitude window feature may be used to extrapolate aircraft tracks that are much more accurate than a track extrapolated with a function that assumes all aircraft will remain unaccelerated.

Figure 2 is an overall functional block diagram of the STARS system of figure 1. The STARS 10 comprises GPS antenna 12, optional GPS antenna 22, GPS receiver 56, GPS processor 58, modem 60, transceiver 62, transceiver antenna 32, optional transceiver antenna 34, STARS computer 66, control unit 68, storage unit 70, input and output interface 72, display unit 74, and audio interface 76. The STARS computer 66 comprises a microprocessor or microcomputer based system having a microprocessor, read only memory (ROM), random access memory (RAM), and input/output ports (I/O ports). It is understood that STARS computer 66 may also comprise any additional circuitry, such as A/D and D/A converters, combinational logic circuitry, latching circuitry, etc., that may be necessary for the operation and interconnection of STARS computer 66 with respect to the components of the STARS 10. All of the above-described

components of STARS computer 66 may be located on an individual semiconductor chip. The STARS 10 may also be located on an individual or plurality of custom VLSI chips. The antenna 12 may be an antenna mounted to the top of the aircraft to receive GPS signals from orbiting satellites. Antenna 22 is an optional antenna mounted to the bottom of the aircraft to receive ground based pseudo-satellite signals. Pseudo-satellite signals can be used to increase the positional and altitude accuracy of the STARS 10 during an airport approach or when the aircraft is flying below dense cloud cover. The GPS receiver 56 is used to determine the aircraft's position (longitude, latitude and altitude). Other types of satellite receivers, such as receivers for receiving signals from the Soviet Glonass satellites, may be used. As well understood by those skilled in the art, each GPS satellite transmits binary pulse trains, copies of which are created in the GPS receiver electronics. The GPS receiver antenna detects the signals (binary pulse trains) transmitted from GPS satellites, amplifies the received signals, and inputs them into two tracking loops that lock onto the carrier waves. The GPS pulse train is adjusted in the tracking loop until it is brought into correspondence with the satellite pulse train. When correspondence is achieved, the GPS receiver resident processor can determine signal travel time based on the pulse adjustment. The GPS receiver resident processor then may determine the pseudo-range (distance from the GPS receiver to each satellite) based on the signal travel time (plus or minus clock bias error) multiplied times signal travel time; (pseudo-range =  $C \times \Delta T$ ). The GPS receiver 56 may then determine its location using four pseudo-ranges, solving four simultaneous equations having four unknowns, as well known to those skilled in the art. The GPS processor 58 may be resident in the GPS receiver or separate. The GPS processor 58 automatically determines the user's current position (longitude, latitude and altitude) tracking and speed.

The GPS receiver 56 should be a multi-channel receiver for receiving positioning signals from a plurality of GPS satellites. A number of GPS receivers are commercially available from such companies as Sony Corporation, Motorola, Rockwell International (the Navcore V GPS receiver), and others. One such commercially available GPS receiver is the Nav 1000 GPS receiver manufactured by Magellan Systems Corporation. The data output by GPS receiver 56 is input to the GPS processor 58.

The GPS processor 58 performs the calculations necessary to determine the

aircraft track, speed, and acceleration, and precision GPS time. The precision GPS time can be found by determining the clock bias error as one of the four unknowns in the standard four equation GPS navigation solution. It is well known in the art how to determine an highly accurate clock from the GPS signals.

5 In the preferred embodiment the STARS 10 uses the absolute time synchronization mode. With absolute time synchronization a special time synchronization is derived from a GPS satellite. Absolute time synchronization can achieve accuracy's of about 100 nanoseconds. GPS synchronized time is used to synchronize the modem 60 with other aircraft STARS. It is understood to those skilled in the microprocessor controller arts that the GPS processor functions may be incorporated into a single faster microprocessor to form an integrated STARS computer/GPS signal processor 66 and 58. Such a high speed microcomputer or digital signal processor is the TMS320C40 or TMS320C50 available from Texas Instruments Incorporated.

15 The modem and data transfer protocol provide communications between STARS. The modem 60 uses a suitable data transmission modulation technique such as frequency shift keying (FSK), pulse position modulation, or quadrature phase shift keying (QPSK) for use with a multiple access protocol. The modulation may be synchronized with GPS precision time. In the preferred embodiment the STARS 10 will transmit and receive on the L-band TCAS interrogator frequency. The multiple access protocol of the preferred embodiment is the time division multiple access protocol (TDMA). TDMA is run by a sequence of computer instructions on the STARS computer 66. The protocol may also execute on its own microprocessor and interface to the STARS processor 66 as a microprocessor peripheral device. The TDMA protocol works by dividing a radio frequency into a fixed number of time slots. For example, a frequency could be divided into 100 time slots where each slot is 1/100 of a second. Since the preferred L-band TCAS frequency is very high, approximately 1 Ghz or 1,000,000,000 cycles per second, a time slot of 1/100 of a second has a theoretical transmission rate of 1 million bits per second. In practice, however, TDMA throughput is some what less than the theoretical limit because of protocol overhead and synchronization time. The preferred STARS TDMA implementation, discussed in substantive detail below, automatically assigns each STARS within a limited direct radio range a TDMA slot. Each STARS transmits



on its assigned slot and receives signals from other STARS on all the other TDMA slots. It is understood that other multiple access protocols such as collision detection re-transmission, spread spectrum techniques and code division multiple access are within the scope of the present invention. The STARS TDMA message  
5 has a general broadcast mode and a specific broadcast or data link mode. In the general broadcast mode the STARS 10 transmits on the appropriate TDMA slot a message that all other STARS receivers within the broadcast range will receive and process. In the specific or data link broadcast mode the STARS transmits, on the appropriate time slot, a message with a specific aircraft identification number  
10 encoded in the TDMA message. All other STARS receivers within the broadcast range receive and process the data link message. If the message encoded aircraft identification matches a STARS aircraft identification then the STARS whose aircraft identification matches the message processes the message as a specific data link message.

15 The display unit 74 may be a CRT or other suitable display such as gas plasma, LCD, or active matrix LCD. In the preferred embodiment the display will fit into the standard aircraft instrument hole and can be mounted in the front aircraft instrument panel. Preferably the STARS 10 electronics are located in a separate housing but it is within the scope of the present invention to house the  
20 STARS electronics in the display unit 74.

The storage unit 70 is a non-volatile computer memory such as flash memory available from Intel Corporation and Texas Instruments Incorporated or volatile RAM with battery back up. The storage unit 70 may also contain the permanent program memory for the STARS program. The STARS program may  
25 be fixed in ROM memory or flash memory. The storage unit 70 may also contain a mass storage device such as a PCI card, floppy disk, or hard disk to store database information. The STARS 10 storage unit 70 may contain a worldwide Jeppesen data base which includes the coordinates of all airports with runways over 1000 feet in length, including airport elevations, VHF, VOR's, and NDB's,  
30 and an expanded database, including information, such as airport VHF communication frequencies, fuel availability, instrument landing system (ILS) details, DMEs, and intersections.

The audio interface 76 contains a digital to analog converter and is connected to the aircraft audio intercom system 78. The audio interface 76 is used

to synthesize speech to notify the aircraft pilot of the STARS alarm status or if necessary the STARS evasive maneuver. A suitable voice synthesizing coder/decoder digital to analog chip is the TSP53C30 available from Texas Instruments. It is understood that there are a wide variety of D/A chips and digital storage  
5 formats available and that these formats and D/A techniques are within the scope of the present invention. In the preferred embodiment the STARS 10 audio alarms may be stored in pulse code modulation or linear predictive coding format. The audio interface 76 is used by STARS 10 to produce audio alarms, synthetic voice alarms and synthetic voice commands into the cockpit via the aircraft intercom  
10 system 78.

The peripheral input and output (I/O) control unit 72 contains the circuits necessary, e.g. parallel and serial digital circuits, A/D converters and switch sensors, to interface the STARS 10 to auxiliary aircraft systems and controls. It is understood that the I/O control unit 72 may be a separate set of integrated circuits  
15 or may be combined as a subsystem to a custom VLSI STARS computer 66. The peripheral equipment interface to the STARS 10 may be an open and close switch, a parallel or serial digital interface from another on-board system, or an analog signal from an aircraft sensor. For example, one such external control interface is to a switch for detecting whether the landing gear is up or down, another is from  
20 an internal high gravity force shock detector. Yet another is from a switch that detects whether the aircraft door or cargo hatch is open. In addition, aircraft subsystems and instrumentation such as data from the ground proximity and wind shear systems, the on-board maintenance computer, the radio altimeter, the roll gyro synchro, the pitch gyro synchro, the magnetic heading synchro, the  
25 barometric pressure altitude, the flight recorder, and the autopilot may be connected to the STARS 10 at the I/O control unit 73. It is understood that some aircraft subsystems such as the roll gyro, pitch gyro, and magnetic heading gyro may use either an analog or digital interface signal and that the A/D conversion necessary to interface the STARS 10 to these systems is within the scope of the  
30 present invention. It is understood that other aircraft systems may be connected to the STARS 10 and that the STARS 10 TDMA transceiver system 62 may transfer and process data from these other aircraft systems.

The STARS computer 66 is a single or multiple microprocessor or microcomputer based system used to execute the STARS programming. As stated

above, in the preferred embodiment the STARS processor may be a TMS320C40 or TMS320C50 general purpose digital signal processor available from Texas Instruments Incorporated. The STARS 10 program is understood to have a multitasking/multiprocessor embodiment as well as a linear program

5 embodiment within the scope of the invention. A multitasking/multiprocessor environment uses a plurality of microprocessors executing computer instructions in parallel with one another. For example, the STARS computer 66 may have a microprocessor for executing the instructions for the TDMA protocol, another microprocessor for executing the instructions for GPS signal processing, and

10 another microprocessor for overall system control that communicates with the TDMA and GPS microprocessors. Thus, the several processors each execute their own particular sequence of instructions (programs) simultaneously, i.e. multitasked. The multiple programs executing on the TDMA and GPS microprocessors may also execute on a single fast microprocessor if the single

15 microprocessor is fast enough to switch between the TDMA and GPS programs to give the two programs the same execution speed as the dual microprocessor configuration, e.g. a multitasked and single processor embodiment. Likewise, all the processing functions TDMA, GPS and control processing may be performed on a single microprocessor if the single microprocessor is fast enough to give all of

20 the processes a sufficient execution speed. In a multitasking environment the multiple processes are executing simultaneously and communicate between processes as if the process are executing independently of one another. Multitasking can be accomplished on a multiprocessor configuration or on a single fast microprocessor. A linear embodiment of the STARS 10 program is also

25 within the scope of the present invention. A linear embodiment of the STARS program is a sequence of instructions that performs all of the necessary STARS processes in a one sequential loop. In the linear embodiment each task, e.g. the TDMA, GPS and control processes, are executed in fast sequence one after another.

30 It is understood that aircraft power is operably connected to the STARS system 10. This includes normal aircraft power at 115 VAC 400 Hz and +28 VDC and emergency aircraft back-up power from the aircraft batteries. Internal STARS battery power may be used for long term variable storage and for emergency beacon power.

Figure 3 shows the display 74 in the relative bearing mode 80. The relative bearing mode 80 displays the relative bearing of intruder aircraft within the STARS 10 tracking range. The relative bearing mode 80 is calibrated with concentric circles 82 representing the range in nautical miles to the intruders representation 84. It is understood that the calibrated marking 86 may change depending on the STARS range mode, discussed below. Intruders that are beyond the calibrated range display are represented in the relative bearing mode 80 as intruders at the very edge of the display 88. The display 74 is preferably a color display capable of sufficiently high resolution to display aircraft in a relative bearing mode 80 as shown in figure 3.

Figure 4 shows the three dimensional altitude and bearing mode 90 on the display unit 74. The three dimensional mode 90 shows the three dimensional track for one's own aircraft representation 92 and intruder aircraft representations 94. The vertical index 96 is calibrated with in feet to show the aircraft altitude. The horizontal index 98 is calibrated to show the range in nautical miles.

Figure 5 shows the STARS 10 control unit 68. The control unit 68 is the user interface for the STARS 10. In the preferred embodiment the control unit 68 is mounted in the aircraft front instrument panel just below the display unit 74. The control unit 68 physical dimensions in the preferred embodiment allows the control unit 68 to fit into a standard aircraft instrument hole. The control unit comprises: alpha-numeric display 100; control knobs 102; buttons 104; control knob 106; and numeric display 108. The knob 106 selects the altitude window that is displayed in numeric display 108.

The altitude window data is used when a STARS extrapolates the track of the host aircraft and any intruder aircraft. Thus, the altitude window information may be used to create more accurate predictions of aircraft tracks. More accurate aircraft track predictions will reduce the number of false collision alarms created by more simplistic track prediction methods such as the TCAS "tau" calculation. The altitude window is the pilot's intended level off altitude. For example, if an aircraft pilot is taking off from an airport and the pilot intends to maintain a standard climb rate and level off at 12,000 feet then the pilot may select with knob 106 the level off altitude, e.g. 12,000 feet. The STARS 10 transmits the altitude window data in the regular STARS 10 TDMA transmission discussed below.

Figure 6 illustrates the STARS 10 control program sequence. The STARS 10

control program sequence is a continues loop comprising the following steps:  
STARS initialization 110, read GPS receiver queue 112, read I/O queue and  
control switches 113, transmit information 114, read receiver queue 116,  
surveillance and tracking function 118, threat evaluation function 120, display and  
5 alert function 112; determination of whether an evasive command is required 124;  
calculation of an evasive command 126; establishing a data link 128; and issuing  
the evasive command 130. The initialization step 110 contains the sequence of  
steps necessary to initialize the STARS 10. The initialization step 110 includes  
10 placing the STARS processor 66, internal registers, I/O units 72, GPS receiver  
processor 58, display unit 74, and control unit 68 to a known predetermined  
initialization state. The initialization step 110, in addition, executes a power on  
self test routine to test the STARS 10, peripheral I/O connections 72, the GPS  
receiver 56, and GPS processor 58, modem 60, and transceiver 62. If the STARS 10  
passes the built in test routine the initialization step 110 allows the control  
15 program sequence to advance to step 112. If the STARS 10 fails the built in test  
then the initialization step 110 causes a diagnostic code that describes which  
STARS 10 component failed to be displayed on the STARS alpha numeric display  
100 and halts further control program execution.

The read GPS receiver queue step 112 in the preferred embodiment may  
20 check a processor register for information from the GPS receiver subsystem. The  
information from the GPS receiver subsystem, i.e. the GPS receiver 56 and GPS  
processor 58, is the aircraft position, altitude, and track in digital data form is  
automatically sent to the STARS computer 66. In the preferred embodiment the  
STARS GPS receiver subsystem executes the GPS program sequence separate and  
25 apart from the STARS control program. Thus, the receiver queue is a set of data  
storage registers contained in the STARS computer 66 interface to the STARS GPS  
processor 58. The receiver queue latches the information from the GPS processor  
58 and serves as a data buffer between the GPS processor 58 and the STARS  
computer 66. The STARS control process at the read receiver queue step 112  
30 moves the data from the receiver queue to an internal STARS computer 66 data  
storage register. This empties the receiver queue data registers and readies the  
data registers for new information. The STARS control process can manipulate  
and use the aircraft position, altitude, and track data as necessary to perform the  
STARS 10 functions in the STARS computer 66 internal registers. The use and

manipulation of the positional and tracking data are described in substantive detail below.

The STARS control program advances to the read I/O queue and control switches step 113. The STARS computer 66 checks the status of the I/O control unit 72 for data. It is understood that temporary data storage and I/O status registers are used in the STARS computer 66 to connect to the I/O control unit 72. The temporary data storage and I/O registers buffer data and facilitate communications between the STARS processor 66 and the I/O control unit 72. The I/O status register may indicate which data register(s) contains new and valid data. For example, if the STARS 10 is connected to another aircraft system such as the radio altimeter, the radio altimeter is connected to the STARS with the I/O control unit 72. The I/O control unit 72 latches the digital data from the radio altimeter into an I/O storage register. The I/O unit then sets a bit in the I/O status register to indicate that digital data from the radio altimeter has been received. When the STARS control process reaches the step 113, the control process reads and decodes the I/O status word. The decoded status word indicates whether data is present from the radio altimeter. The control process may move the data from the I/O control unit 72 data register to an internal storage register or to the storage unit 70. The STARS control process 113 may set or clear the I/O status word to represent that the data has been moved from the I/O control 72 storage register and that the storage register is now free to receive more data. Thus, the I/O control unit 72 data and I/O status registers serve as buffers between the fast execution of the STARS control program and relatively slow speed of STARS 10 I/O communications. Likewise, the STARS computer 66, at step 113, scans the control unit 68 switches.

The STARS control program now advances to the transmit information step 114. In the preferred embodiment, the transmit information step 114 comprises the sequence of instructions necessary to format a STARS 10 TDMA message and transfer the message to the STARS transmitter system 132. The STARS transmitter system comprises the modem 60 and transceiver 62. The STARS message comprises a block of digital data with the following encoded data fields: a synchronizing pattern; the sending aircraft identification; the receiving aircraft identification; a control word; longitude data; latitude data; altitude data; velocity x; velocity y; velocity z; altitude window; user programmable telemetry; a status

message; and a cyclic redundancy check (CRC) field. The construction of the STARS message block is discussed in substantive detail below.

The STARS control program now advances to read the receiver queue 116. The read receiver queue step 116 in the preferred embodiment may check a processor register for information from the transceiver 62 and modem 60. The information from the transceiver 62 and modem 60 is STARS message blocks from other STARS equipped vehicles in receiving range. As discussed in substantive detail below, the transceiver 62 and modem 60 executes the tasks necessary to receive and transmit messages with other STARS separate and apart from the STARS control program. Thus, the transceiver queue is a set of data storage registers contained in the STARS computer 66 interface to the STARS modem 60. The transceiver queue latches the information from the modem 60 and serves as a data buffer between the modem 60 and the STARS computer 66. The STARS control process at the read receiver queue step 116 moves the data from the receiver queue to an internal STARS computer 66 data storage register. This empties the receiver queue data registers and readies the data registers for new information. The STARS control process can manipulate and use the messages from other STARS as necessary to perform the STARS 10 functions in the STARS computer 66 internal registers.

The surveillance and tracking function 118, discussed in substantive detail below, processes the data blocks received in step 116. This includes determining the range of any intruder aircraft, determining the relative bearing, determining the relative altitude, calculating the closing rate, deciding whether the intruder should be put into the tracking mode, and calculating an estimate miss distance.

The threat evaluation function 120, discussed in substantive detail below, divides all intruder aircraft into a threat classification. The threat classifications are non-threat, proximity, traffic advisory, and resolution advisory threat.

The display and alert function 122, discussed in substantive detail below, generates the display of the intruder aircraft for the display unit 74 and generates the pre-programmed audio alerts with the audio interface 76.

The determination whether an evasive command is required at step 124 is based on a list of pre-determined parameters discussed in substantive detail below. Generally, the altitude of the aircraft and the calculated miss distance will determine whether the STARS will issue an evasive command.

The calculation of an evasive command 126, discussed in substantive detail below, generally depends on which aircraft is at the higher altitude and aircraft performance factors.

The establishment of a data link 126, discussed in substantive detail below,  
5 is used to coordinate evasive maneuvers between aircraft. The coordination of evasive maneuvers assures that aircraft on a collision course will increase their separation by the execution of a coordinated evasive maneuver.

The issuance of the evasive command 130, discussed in greater detail below, is the alert and display of the evasive maneuver to the pilot. The evasive  
10 command issues after the coordination of the evasive command 128.

Figure 7 illustrates the STARS data message block sent and received by the STARS control program shown in figure 6. The STARS data block comprises a synchronizing pattern 140, a sending aircraft identification 142, a receiving aircraft identification 144, a control word 146, longitude data 148, latitude data 150,  
15 altitude data 152, velocity X 154, velocity Y 156, velocity Z 158, altitude window 160, telemetry 162, a message 164 and a CRC character 166. The synchronizing pattern 140 is a predetermined synchronization pattern that indicates the start of STARS data block. The synchronization pattern is the same for all STARS data blocks, therefore, when a STARS transceiver recognizes the synchronization  
20 pattern it synchronizes the receiver queue with the start of the STARS message. The aircraft ID field 142 is a digital word that encodes the full aircraft registration number of the transmitter STARS aircraft. Block 142, in addition, contains encoded information about the aircraft model. For example, N1234567B727 represents the registration number of an aircraft, e.g. N1234567, and that the aircraft is a Boeing 727, e.g. B727. The aircraft ID receiving field 144 is the  
25 registration number for a targeted intruder aircraft. This field 144 is used to designate whether the data block is a general STARS location beacon message or a STARS data link message. The data link message is used to coordinate resolution advisory commands between aircraft. The data link block contains information  
30 for communication between two particular aircraft, whereas, a general STARS beacon message is directed to all aircraft and ground sites within receiving range. The control word 146 is used in conjunction with the aircraft receiving ID 144 to coordinate the data link and resolution advisory. The control word 146 also identifies whether the STARS message is a general poll, data link, or an ATC



message. The control word 146 can also be used to prioritize a message or encode emergency indications. The longitude data field 148 is data that represents the GPS longitude of the aircraft. The latitude data field 150 is data that represents the GPS latitude of the aircraft. The altitude data field 152 is data that represents the GPS altitude of the aircraft. It is important to note that the longitude, latitude, and altitude data is from the GPS receiver system and not from a solely internal aircraft reference such as the inertial navigation system (INS) or a pressure altimeter. A GPS commercial grade receiver may have resolution errors in its positioning calculations. These resolution errors, however, are inherent in the GPS methodology and therefore are common to all commercial grade GPS receivers operating in the same geographic area. Since all STARS GPS receivers have the same commercial grade resolution error, when the position and tracking information are used to calculate relative distance between aircraft the resolution error cancels. This makes the STARS 10 local GPS beacon method of the present invention extremely accurate at determining the relative location and altitude of intruder aircraft. The velocity X 154, velocity Y 156, and velocity Z 158 data fields together represent the velocity vector of the aircraft. The velocity vector is calculated by continuously measuring the distance between GPS positions divided by the time the aircraft took to cover the distance. The altitude window 160 represents the "fly to" altitude of the aircraft. The altitude window 160 data is input from the STARS control panel 68. As pointed out earlier, a source of numerous false alarms in present anti-collision systems arises from a condition where one aircraft is taking off and climbing and another aircraft is descending. The alarm is false because the climbing aircraft may level out at a predetermined altitude and, therefore, present no collision danger. The present invention overcomes this limitation by allowing the pilot to designate in advance the predetermined level off altitude on the STARS control panel 68. A STARS transmits this information in the altitude window field 160. STARS processors use the altitude window 160 information to determine the extrapolated trajectory of aircraft and whether a resolution advisory should be generated. The telemetry field 162 represents data that encodes selected aircraft telemetry. For example, whether the landing gear up or down may be encoded in this field. It is within the scope of the present invention to send and receive other instrumentation or other aircraft system data within the telemetry data field. The message field 164

represents data that encodes messages and is otherwise reserved as a maintenance channel and for future use. It is understood that a data block (CRC) 166 can be included with the data block transmission. A CRC check field assures, to a high degree of probability, that the data block is received without bit errors. Thus, data blocks with bad CRC fields can be rejected as blocks having bit error(s). It is also within the scope of the present invention that data coding, such as, forward error correction (FEC) and other noise immunity techniques can be employed to improve the effective signal to noise ratio of the STARS signal. For example, the Reed-Solomon FEC algorithm can be used to make a more robust data sequence.

Figure 8 illustrates the TDMA protocol sequence. The STARS 10 at power on and when placed into active beacon mode will initialize the transmission protocol 166 by setting data registers and protocol procedures to a predetermined initial state. In the preferred embodiment, the TDMA protocol is used to synchronize STARS beacon and data link signals. It is understood to those in the art, however, that other suitable multiple access protocols are within the scope of the present invention. The TDMA protocol initially scans the beacon frequency for open time slots 168. After listening for six TDMA cycles 170 the protocol identifies a time slot that has been open for six consecutive cycles 172. The TDMA protocol seizes the time slot by transmitting a data block shown in figure 7 to the modem 60 at the precise time slot. It is understood that a FEC coder/decoder maybe inserted at this point. The modem 60 modulates the beacon frequency carrier for the transceiver 62 to broadcast through the beacon antenna 32. The TDMA protocol will continue to beacon the data block at it's seized TDMA slot for a randomized number from three to nine TDMA cycles 180. It is understood that the carrier frequency should be sufficiently high to support multiple TDMA time slots. In the preferred embodiment the STARS 10 transmits on the TCAS L-Band interrogator SHF radio frequency, however, a laser, infrared, UHF or VHF carrier is within the scope of the invention. When the transmission cycle is complete 180, the TDMA protocol listens for whether its seized TDMA slot is clear 182. If the slot is clear the protocol keeps the slot and returns to the beacon mode 176. If the slot is not clear the TDMA protocol returns to the scan mode 168 and begins to scan for another free slot. Thus, the TDMA protocol synchronizes into the TDMA slot by finding a clear TDMA channel and transmitting it's data block in that slot. During transmission the transceiver 62 blanks the receiver input to prevent

receiver overload. When the TDMA protocol and transceiver 62 stops transmission on the seized time slot it immediately returns to the listen mode to receive beacons from other STARS systems. When the TDMA protocol decodes a beacon on another slot it places the received data block into the receiver queue

- 5 116. It is understood that the transmission time slot is relatively small when compared to the total number of available slots. Thus, the receiver queue 116 is understood to be large enough to accommodate a plurality of incoming messages. It is also understood that the TDMA protocol requires precise timing to obtain the maximum number of time slots available at any given frequency and burst size.
- 10 The GPS precision clock provides an excellent source of precision timing signals to maintain a single timing source for all STARS within a given geographic area and thus maximize the TDMA synchronization between STARS.

- Figure 9 illustrates the sequence of instructions required to execute the surveillance and tracking function shown in figure 6. The surveillance and
- 15 tracking function 118 comprises the sequence of instruction necessary to: determine the range to all aircraft in the STARS receiving range 186, determine the relative bearing to all intruders 188, determine the relative altitude of intruders 190, calculate aircraft closing rates 192, determine whether the aircraft should be placed into the track mode 194; calculate the relative position 198, calculate the
- 20 altitude closing rate 200, and estimate the miss distance 202. The surveillance and tracking function 118 function first determines the range 186 of intruding aircraft. Range is determined by calculating the length of the vector between the intruder aircraft position and altitude and one's own aircraft position and altitude. The function next calculates the relative bearing 188 of the intruder aircraft. The
- 25 relative bearing is calculated by determining the angle of the intruder aircraft relative to the baseline zero degree angle directly ahead of one's own aircraft. This calculation is performed by determining the X and Y displacement from one's own location to the intruder aircraft. The displacement is adjusted for the display units 74 distance calibration 86 and is used to display the intruder aircraft
- 30 in the relative display mode 80. The function 118 next calculates the relative altitude between one's own aircraft and an intruder aircraft at step 190. The relative altitude 190 may be calculated by using the Z component of the vector distance between one's own aircraft and the intruder aircraft. The function 118 next calculates the closing rate of the intruder aircraft at step 192. The closing rate

is determined by subtracting the velocity vector of one's own aircraft from the intruder aircraft. Thus, aircraft velocity vectors that are pointed at each other will have an additive velocity effect. While two velocity vectors pointed in the same direction will have a set off effect on the closing rate. The function 118 next  
5 determines whether the intruder aircraft should be put into the track mode at step 194. This determination is made by comparing the aircraft altitude, bearing, and closure rate to predetermined parameters. In the preferred embodiment the predetermined parameters are whether the intruder is within 80 miles of one's own aircraft. If the intruder aircraft falls within the predetermined parameters the  
10 intruder aircraft is put into track mode and the function proceeds to step 198. If the intruder aircraft falls outside of the predetermined track thresholds at step 194 then the function 118 returns to the main loop 196. If the intruder is put into track mode then the function 118 calculates the relative position of the intruder aircraft at step 198. The relative position of an intruder aircraft is the X and Y vector  
15 displacement between the intruder aircraft and one's own aircraft. The function 118 then calculates the altitude closing rate at step 200. The altitude closing rate is the value of the Z component of the difference between one's own aircraft velocity vector and the intruders velocity vector. The function 118 next estimates the miss distance between an intruder aircraft and one's own aircraft at step 202. This may  
20 be performed by step 202: extrapolating the trajectory of the intruder aircraft from the intruder aircraft position, velocity vector, and altitude window data; extrapolating one's own aircraft trajectory from one's own position, velocity vector, and altitude window data; and using the extrapolated trajectories to determine the closest distance between the two aircraft trajectories by iteratively  
25 calculating the distance from a point on one's own track to each point on the intruders track. The surveillance and tracking function 118 then returns at step 204 to the STARS control program shown in figure 6. The STARS control program then calls the threat evaluation function 120.

Turning now to figure 10, data calculated in the surveillance and tracking  
30 function 118 is passed to the threat evaluation function 120. Depending on the altitude, position, closure rates, and velocity vector and the STARS sensitivity mode, discussed below, the threat potential and evaluation function 120 categorizes at step 206 intruder aircraft as either a resolution advisory threat 208, a traffic advisory 210, proximity 212, or a non-threat 214. If it is determined that the

intruder aircraft is a non-threat 214 then the system returns from the function at step 216. If it is determined that the intruder is outside the traffic advisory parameters but within the predetermined proximity parameters then the intruder is classified as a proximity threat 212. The function 212 flags the intruder aircraft  
5 for a proximity alert on the display. If the intruder aircraft is within the traffic advisory parameters but outside the resolution advisory parameters then the function 210 will flag the intruder aircraft for a traffic advisory display. If the intruder aircraft is within the resolution advisory parameters then the intruder aircraft is flagged as a resolution advisory. The categorized intruder aircraft are  
10 then passed to the display and alert routine 122. It is understood that all intruder aircraft are tracked simultaneously and that the data may be stored in an array of data organized by the intruder aircraft identification number (ID).

Figure 11 illustrates the sequence of steps necessary to perform the display and alert function 122 shown in figure 6. The display and alert function 122  
15 comprises the following steps: create a resolution advisory (RA) tracking display 226; create a traffic alert (TA) tracking display 228; create a tracking display for proximity alerts 230; create a tracking display for non-threats 232; create an audio alert for a resolution advisory 236; create an audio alert for a traffic advisory 234; create a display for an "evasive maneuver" 242; create a display for "traffic" 244;  
20 create a display to highlight an RA target 246; and create a display to highlight a TA target 248. The display and alert function 122 uses the classification from the threat evaluation function 120 to divide intruder aircraft records into the resolution advisory 218; traffic advisory 220, proximity alert 222, or non-threat 224 categories. If the intruder aircraft is classified as an resolution advisory 218 the  
25 function 122 creates an RA tracking display 226, creates and audio alert 236, creates a display to display "evasive maneuver" 242 and displays the intruder target as a highlighted icon 246. The function to create an RA tracking display 226 reads the intruder aircraft ID, range, altitude, and time to point of contact (TPOC) from the intruder aircraft data record. Function 226 formats and sends this data to  
30 the STARS display unit 74. The audio alert function 236 creates a synthetic voice stating "alert, alert ..." and sends this information to the STARS audio interface 76. The function 242 creates and an "evasive maneuver" display for the STARS display unit 74. The "evasive maneuver" display appears as flashing text across the bottom of the STARS display 74 and indicates that an evasive maneuver is

imminent. The display target highlight function 246 displays the intruder aircraft representation on the display unit 74 as bright and flashing. If the intruder aircraft is classified as a traffic advisory 220 the display and alert function 122 executes the following steps: create a TA tracking display 228, create and audio  
5 alert 234, create a display "traffic" 244, and display a target highlight 248. The create TA tracking display 228 function reads the intruder aircraft ID, range, altitude, and TPOC from the intruder aircraft data record. The function 228 formats and sends this data to the STARS display unit 74. The traffic advisory creates a synthetic voice audio alert to announce "traffic, traffic, ..." over the  
10 aircraft intercom system. The audio alert 234 function sends the synthetic voice commands to the audio interface 76. The display function 244 creates a "traffic" display at the bottom of the STARS display unit 74. If the intruder aircraft is classified as a proximity alert 222 function 230 creates a tracking display. The function 230 creates a tracking display of the intruder aircraft for display on the  
15 STARS display unit 74. The display is a dot that represents the relative bearing and distance to the intruder aircraft. If the display and alert function 122 classifies the intruder aircraft as a non-threat 224 then the function creates a tracking display for a non-threat aircraft at step 232. The tracking display 232 step creates a dot that represents the intruder aircraft at the edge of the STARS display unit 74.  
20 The dot represents the relative bearing to the intruder aircraft and that the intruder aircraft is outside the display unit 74 calibrated display range. The function 122 returns to the control program illustrated in figure 6 at step 250.

Figure 12 illustrates the steps necessary to calculate an evasive command as shown in figure 6 step 126. The calculate evasive command function 126  
25 comprises the following: determining if the intruder aircraft is higher 254, reading the altitude window information 256, determining aircraft performance data 258; calculating aircraft altitude 260, and determining an evasive maneuver for one's own aircraft 262. The calculate evasive command function 126 calculates an initial evasive command by determining which aircraft is at a higher GPS altitude at step  
30 254. The calculate evasive command function at step 254 tentatively determines that the higher aircraft will be issued the climb command and the lower aircraft will coordinate with a descend command. The function 126 then retrieves the altitude window information at step 256, the aircraft performance data at step 258 and the aircraft altitude at step 260 from the STARS 10 memory and storage unit

70. The function 126 determines at step 262 using these factors and a set of predetermined parameters whether the initial evasive maneuver calculated in step 254 is permissible. If the initial evasive maneuver calculated at step 254 is permissible the evasive command function 126 returns with the initial evasive maneuver at step 264. If the function at step 262 determines that the initial evasive maneuver calculated at step 254 is impermissible then step 262 determines a permissible evasive maneuver. It is understood that the evasive maneuver generator will generate an evasive command that requires the least radical maneuver. For example, if two aircraft are at the same altitude but one aircraft is descending, the evasive command will allow the descending aircraft to keep descending and order the possibly lower aircraft to climb. The function 126 then returns with the permissible evasive maneuver calculated at step 262 at step 264.

Turning back to figure 6 the calculate evasive command function 126, shown in detail at figure 12, returns with an evasive command. The STARS control process shown in figure 6 advances to the establish data link step 128. The data link step 128 sends the evasive command generated for one's own aircraft to the intruder aircraft. This is accomplished by formatting a standard STARS data block, shown in figure 7, with the intruder aircraft ID in the receiving aircraft data field 144. More specifically, the establish data link function 128 builds a TDMA transmit block as follows: one's own aircraft ID is encoded in field 142; the receiver aircraft ID field 144 is programmed with the intruder aircraft ID, the control word 146 is encoded with a pattern that indicates an initial evasive maneuver data link command, fields 148, 150, and 152 are encoded with the respective longitude, latitude, and altitude data of one's own aircraft; the velocity vector fields 154, 156 and 158 are encoded with data that represents the evasive maneuver velocity vector calculated at step 126. This message is sent by the STARS control program to the STARS modem 60 for transmission by the transceiver 62.

STARS within receiving range receive the TDMA data link message sent at step 128. Receiving STARS, e.g. intruders, scan the receiving aircraft ID field 144 to determine if the message has a receiving aircraft ID 144 that matches it's own unique aircraft ID. If the IDs match, the STARS decodes the control word 146 and the evasive maneuver velocity vector encoded in fields 148, 150, and 152. The receiving STARS then creates an evasive maneuver that is opposite to the other

aircraft's altitude change. For example, if one's own aircraft originally generates an evasive maneuver to climb then the opposite evasive maneuver generated by an intruder aircraft would be to descend. The receiving STARS builds a TDMA data reply block as follows: The sending aircraft ID field 142 is encoded with the intruder aircraft's ID; the receiver aircraft ID field 144 is programmed with the aircraft sending ID field decoded from the received data link block 142; the control word 146 is encoded with a pattern that represents an evasive maneuver data link acknowledgment; fields 148, 150, and 152 are encoded with the positional data; field 154, 156 and 158 are encoded with data that represents an evasive maneuver velocity vector. The receiving STARS transmits this "acknowledgment" message.

The originating STARS receives the acknowledgment message and the opposite evasive maneuver from the receiving STARS, e.g. the intruder STARS. When the evasive maneuver originating aircraft receives the data link acknowledgment with an opposite maneuver the originating aircraft at step 128 creates and formats the evasive maneuver for display on the STARS display unit 74. The originating STARS also creates the appropriate audio message with the audio interface unit 76. A contrary maneuver from the intruder indicates that the evasive command was rejected and the data link originating aircraft should display an opposite maneuver. Appropriate evasive maneuver synthetic voice commands and corresponding display are as follows:

"CLIMB" "CLIMB", "DESCEND" "DESCEND"  
"STOP CLIMB", "STOP CLIMB"  
"STOP DESCEND", "STOP DESCEND"  
"DO NOT CLIMB", "DO NOT CLIMB"  
"DO NOT DESCEND", "DO NOT DESCEND"

If the STARS command is a reversal of a preceding command then the STARS uses a special reversal command notice. Reversal evasive commands can be generated in high traffic areas where repetitive evasive maneuvers are required between multiple aircraft to assure safe distance. Generally, reversal commands are created that could require the executing aircraft to sustain approximately +/- .35 G. When a reversal vertical maneuver is required, one of the following appropriate evasive commands will be issued.

"CLIMB NOW", "CLIMB NOW"  
"DESCEND NOW", "DESCEND NOW"



- The STARS evasive command generator 126 operates in different modes for different altitudes. Lower layers have less sensitive RA and TA threshold levels to prevent unnecessary advisories in higher traffic density areas. These parameters can be delineated, however, it is understood that these parameters are subject to
- 5 FAA regulatory approval and frequent changes are within the scope of the present invention. The sensitivity modes are:

Sensitivity Level 1

- Own aircraft is below 500 feet above programmed/selected reference altitude (P/S/REF/ALT). In this mode only TAs are generated and RAs are
- 10 inhibited. A TA is generated if (1) the STARS calculates that at the current closing rate a safe miss distance of 1200 feet in relative GPS altitude between one's own aircraft and intruder aircraft will be violated in 20 seconds or less or (2) if the STARS determines that separation between one's own aircraft and intruder aircraft is less than 1200 feet in GPS Altitude.

15 Sensitivity Level 2

- Own aircraft is between 500 feet above P/S/REF/ALT and 2500 feet above P/S/REF/ALT, in this mode TAs and RAs will be generated. A TA is generated if the STARS calculates that (1) at the current closing rate a safe miss distance of 1200 feet in relative GPS altitude between one's own aircraft and intruder aircraft
- 20 will be violated in 35 seconds, (2) separation between one's own aircraft and intruder aircraft is less than 1200 feet in GPS altitude and less than 0.35 NM (2128 feet) in range. A RA is generated if the STARS calculates that (1) at the current rate of closure a safe miss distance between one's own aircraft and intruder aircraft will be violated in 20 seconds or less, and (2) the extrapolated aircraft
- 25 tracks have a miss distance between 400 and 700 feet. A corrective (RA) evasive command will be generated if (1) the extrapolated aircraft tracks determine an aircraft miss distance is less than 400 feet and (2) separation between one's own aircraft and intruder aircraft is less than 750 feet in altitude and less than 0.35 NM (2128) in range.

30 Sensitivity Level 3

- Own aircraft altitude is above 2500 feet P/S//REF/ALT and below 10,000 feet above P/S/REF/ALT. In this mode TAs and RAs will be generated. A TA is generated if the STARS calculates that (1) at the current closing rate a safe miss distance of 1200 feet in relative GPS altitude between one's own aircraft and

intruder aircraft will be violated in 40 seconds, (2) separation between one's own aircraft and intruder aircraft is less than 1200 feet in altitude and less than 0.55 NM (3344 feet) in range. A RA is generated if the STARS calculates that at the current closure rate a safe miss distance between one's own aircraft and intruder aircraft will be violated in 25 seconds. A preventative RA evasive command will be generated if the extrapolated miss distance is between 400 and 700 feet. A corrective (RA) evasive command will be generated if (1) the extrapolated miss distance is less than 400 feet or (2) separation between own aircraft and intruder aircraft is less than 750 feet in altitude and less than 0.55 NM (3344 feet) in range.

10 Sensitivity Level 4

Own aircraft altitude is above 10,000 feet P/S/REF/ALT and below 20,000 feet above P/S/REF/ALT. In this mode TAs and RAs will be generated. A TA is generated if the STARS calculates that (1) at the current closing rate a safe miss distance of 1200 feet in relative GPS altitude between one's own aircraft and intruder aircraft will be violated in 45 seconds or (2) separation between one's own aircraft and intruder aircraft is less than 1200 feet in altitude and less than 0.8 NM (4864 feet) in range. A RA is generated if the STARS calculates that (1) at the current closure rate a safe miss distance between own aircraft and intruder aircraft will be violated in 30 seconds. A preventative RA evasive command will be generated if miss distance is between 500 and 750 feet. A corrective (RA) evasive command will be generated if (1) the miss distance is less than 500 feet. or (2) extrapolated separation between one's own aircraft and intruder aircraft is less than 750 feet in altitude and less than 0.8 NM (4864 feet) in range.

Sensitivity Level 5

25 Own aircraft altitude is above 20,000 feet P/S/REF/ALT and below 30,000 feet above P/S/REF/ALT. In this mode both TAs and RAs will be generated. A TA is generated is the STARS calculates that (1) at the current closing rate a safe miss distance of 1200 feet in relative GPS altitude between own aircraft and intruder aircraft will be violated in 45 second or (2) separation between own aircraft and intruder aircraft is less than 1200 feet in altitude and less than 1.10 NM (6688 feet.) in range. A RA is generated is the STARS calculates that at the current closure rate a safe miss distance between one's own aircraft and intruder aircraft will be violated in 35 seconds. A preventative RA evasive command will be generated if miss distance is between 640 and 850 feet. A corrective (RA)

evasive command will be generated if (1) the miss distance is less than 640 feet or (2) the extrapolated separation between one's own aircraft and intruder aircraft is less than 1200 feet in altitude and less than 1.10 NM (6688 feet) in range.

Sensitivity Level 6

5           Own aircraft altitude is above 30,000 feet P/S/REF/ALT. In this mode both TAs and RAs will be generated. A TA is generated is the STARS calculates that (1) at the current closing rate a safe miss distance of 1200 feet in relative GPS altitude between own aircraft and intruder aircraft will be violated in 45 seconds or (2) separation between one's own aircraft and intruder aircraft is less than 1200  
10 feet in altitude and less than 1.10 NM (6688 feet) in range. A RA is generated is the STARS calculates that at the current closure rate a safe miss distance between own aircraft and intruder aircraft will be violated in 35 seconds. A preventative RA evasive command will be generated if the extrapolated miss distance is  
15 if (1) the miss distance is less than 740 feet or (2) separation between one's own aircraft and intruder aircraft is less than 1200 feet in altitude and less than 1.10 NM (6688 feet) in range.

Figure 13 shows a second embodiment of the present invention wherein the disclosed STARS apparatus and method could be deployed as a ship anti-collision  
20 system. The Ship Satellite Tracking Alert Resolution System (SSTARS) 266, is a self contained shipboard traffic alert and collision avoidance system that utilizes the same methods and apparatus as the STARS 10 but with several changes to adapt the STARS operation to ships.

As well know to the art, large sea going vessels such as supertankers and  
25 container ships require a substantial distance to stop or change course. For example, a fully laden supertanker may require several miles to stop. Therefore, it is critical that large vessels coordinate their movements with other vessels in the area while maintaining a safe distance from navigational hazards such as reefs and sand bars. Typically the coordination of ships is conducted by two way voice  
30 radio communication with the harbor master. However, as shown in the EXXON Valdez disaster this system is an inadequate collision avoidance method especially in remote areas.

The SSTARS 266 may use the same hardware configuration as the STARS  
10. The SSTARS 266 has a three GPS receiver configuration. In the three receiver

configuration the receiver antennae are separated by a predetermined distance, for example, one forward 272, one mid-ship 270, and one aft 268. Since the distance between the receiver antennae is known the SSTARS 266 can constantly check whether the receivers are functional by verifying that the reported distance  
5 between the receiver antennae remains a constant predetermined distance. Should a receiver report a distant that does not correspond to the other two then that receiver can be disabled. Therefore, the three receiver configuration may be used to continuously check GPS receiver operation.

The SSTARS 266 receives satellite navigational signals on receiver antennae  
10 272, 270, and 268. The SSTARS 266 compares the positions from the receivers to the predetermined distance between the receiver antennae. The SSTARS 266 formats a message as illustrated in figure 7. The SSTARS 266 message is the same as the STARS 10 with additional information encoded in the message section 164. The additional information encodes the ship's length height, tonnage, lading, turn  
15 rate, and draw. This information is used by the SSTARS evasive maneuver generator program to generate navigational evasive maneuvers to keep ships separated. Generally, a lighter tonnage ship in the SSTARS embodiment will be given the more aggressive evasive command while a large vessel is given a more minor course correction. The SSTARS embodiment also equips fixed navigational  
20 hazards such as reefs, shoals, and sand bars with a SSTARS 266 type apparatus. It is understood that the SSTARS storage device contains geographic maps. A standard SSTARS can be used to track molecular navigational hazards such as icebergs. The SSTARS fixed navigational embodiment may be preprogrammed with a fixed position, i.e. a fixed navigational hazard does not need to  
25 continuously update and track its own movements since it is fixed. The fixed embodiment also offers the advantage of allowing the collision avoidance system to avoid collisions with temporary or newly occurring navigational hazards such as newly formed sand bars that are not on navigational maps.

The fixed embodiment, in addition, may allow the SSTARS to correlate an  
30 internal topographical SSTARS database (a Map) with a known fixed SSTARS beacon signal. The SSTARS 266 database may contain information concerning ports, port master frequencies, topographical maps of the water ways, water hazards, and seasonal information. The SSTARS transceiver system operates primarily with frequencies for line of sight distance operation i.e. in the UHF,

VHF, or SHF frequency range. For example, the line of sight limitation for a ship with a 200 feet. tall transmit antenna and another ship with a 200 feet receiving antenna is approximately 40 miles. However, it is without the scope of the invention that the SSTARS may use HF frequencies and sky-wave propagation to

5 give the SSTARS a long range mode.

Thus, the SSTARS can act like a radio warning lighthouse to alert passing ships of dangerous waters.

What is claimed is:

1. A method of vehicle collision avoidance using satellite navigational signals and direct radio communication comprising the steps of:
  - determining a first vehicle position with a plurality of satellite navigation signals;
  - determining a second vehicle position with a plurality of satellite navigation signals;
  - encoding and transmitting a direct radio messages that includes said first vehicle identification and position;
  - receiving and decoding a direct radio message that includes said second vehicle identification and position;
  - determining by relative vehicle positions and headings an evasive maneuver to keep said vehicles separated a predetermined distance.
2. The method of claim 1 further comprising the steps of:
  - encoding and transmitting a direct radio message that includes said first vehicle evasive maneuver;
3. The method of claim 2 further comprising the steps of:
  - receiving and decoding a direct radio message that includes said second vehicle evasive maneuver.
4. The method of claim 1 further comprising the steps of:
  - displaying the relative position of said vehicles as a graphic representation showing the relative bearing and distance on a display unit.
  - synthesizing an audio alert that informs the pilot of said evasive maneuver.
5. The method of claim 1 wherein:
  - said vehicle is an aircraft;
  - said satellite navigation signals are from earth based pseudo-satellites;
  - said evasive maneuver is a directive to change the altitude of said vehicles.
6. The method of claim 1 wherein:
  - said vehicle is a sea going vessel;
  - said satellite navigation signals are from earth based pseudo-satellites;

said evasive maneuver is a directive to change the course of said vehicle.

7. A method of vehicle collision avoidance using navigational satellite signals and direct radio wave communication comprising the steps of:

- 5               determining a fixed position with a plurality of navigational signals;  
              encoding and transmitting a direct radio message that includes said  
              fixed position;  
              receiving and decoding said direct radio message;  
              determining by vehicle position and heading an evasive maneuver  
10       to direct said vehicle away from said fixed position.

8. The method of claim 7 further comprising the steps of:

              displaying the relative bearing and distance of said fixed position on  
              a display unit wherein: said fixed position marks a navigation obstacle and  
              navigation marker.

15   9. The method of claim 7 wherein:

              said encoding and transmitting a direct radio message that  
              includes said fixed position includes a unique identification code and code  
              representing the type of navigational hazard;

              said vehicle position is determined from a plurality of satellite  
20       navigation signals.

10. The method of claim 7 further comprising the steps of:

              encoding and transmitting said evasive maneuver;  
              receiving and decoding an evasive maneuver confirmation signal.

11. An apparatus for vehicle collision avoidance with other like equipped vehicles  
25       using satellite navigation signals and a direct radio wave message comprising:

              a satellite receiver for receiving satellite navigation signals;  
              a control program to format the direct radio wave message and  
              determine an evasive maneuver;

              a computer electrically connected to said satellite receiver for  
30       processing signals from said satellite receiver and executing said control  
              program;

              a modem electrically connected to said computer for transmitting  
              and receiving the direct radio wave message from the other like equipped  
              vehicles;

a transceiver electrically connected to said modem to transmit and receive data.

12. The apparatus of claim 11 further comprising:

a display unit electrically connected to said computer to display the relative bearing and distance of the equipped vehicles;

an audio interface electrically connected to said computer to synthesize audio alarms;

a control unit electrically connected to said computer to program and control the collision avoidance apparatus.

13. The apparatus of claim 12 wherein:

said direct radio message is a time division multiple access protocol message;

said modem is synchronized to said satellite receiver clock.

14. The apparatus of claim 11 wherein:

said direct radio message is a time division multiple access protocol message;

said modem is synchronized to said satellite receiver clock.

15. The apparatus of claim 11 wherein:

said computer comprises: a first microprocessor for satellite signal processing electrically connected to a second microprocessor for executing the control program.

16. The apparatus of claim 15 further comprising:

a third microprocessor electrically connected between said second microprocessor and said modem for executing the direct radio wave communication protocol.

17. The apparatus of claim 11 wherein:

said direct radio wave is a skywave; and

said satellite navigation signals are from ground based pseudo-satellites.



1 / 13




FIGURE 1

2 / 13




FIGURE 2

3 / 13




FIGURE 3

4 / 13




FIGURE 4




FIGURE 5

6 / 13




Figure 6

7 / 13




FIGURE 7

8 / 13




FIGURE 8



9 / 13




FIGURE 9

10 / 13




FIGURE 10

11 / 13




FIGURE 11

12 / 13




FIGURE 12

13 / 13




FIGURE 13

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/10375

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G06F 17/40, G01S 3/02

US CL : 364/461, 364/449, 364/452, 340/961, 342/450, 342/451

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 364/461, 364/449, 364/452, 340/961, 342/450, 342/451

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS (GPS, COLLISION AVOIDANCE, DATA, TRANSMIT? AND RECEIV?, LOCATION)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	US, A, 5,153,836 (FRAUGHTON ET AL.) 06 October 1992, ABSTRACT, FIGS. 1A, 1B, 3, COL. 4, 5 AND 22, FIG 3, COLS. 4 AND 5.	1-12, 17 13-16
A	US, A, 4,380,050 (TANNER) 12 April 1983, ENTIRE DOCUMENT.	1-17
A,P	US, A, 5,351,194 (ROSS ET AL.) 27 June 1994, ENTIRE DOCUMENT	1-17



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be part of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

13 OCTOBER 1995

Date of mailing of the international search report

24 NOV 1995

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

THAI PHAN

Telephone No. (703) 305-3800